


Single Phase DB Available in 2 models



Type
Single Door
Double Door

Range
4, 6, 8, 12, 16 ways


Three Phase DB Type Horizontal Available in 2 model



Type
Single Door
Double Door

Range
4, 6, 8, 10,12,16 ways

Three Phase DB Type Vertical Available in 2 model



Type
Single Door
Double Door

Range
4, 6, 8, 12, ways

CONSUMER UNIT Range



SPN 4, 6, 8, 12, 16 ways

METAL ENCLOSURES / PLASTIC ENCLOSURES



1/2 Ways
3/4 Ways

MCCB DISTRIBUTION BOARD



63A/100A, 200A/320A,
400A, 630A

BUS BAR CHAMBERS



RANGE 63A TO 1000A 415V A.C.
CONFORMS TO IS 8623
ENCLOSURES IP 21 CATEGORY



MCB Distribution System

SALIENT FEATURES

Breaking Capacity 10KA

Energy Saving 30- 70% lower Watt loss then specified in IEC

Quick make & Quick break trip free mechanism

Knob Sealing facility available

Din Clip insulated two position type for ease in wiring

RANGE : 6A to 63A curve B / 6A to 63A curve C

POLES : SP, DP, TP, FP, SPN & TPN

RATED VOLTAGE : 240 / 415V AC, 220V DC conforms to IS/IEC-60898-1

ISOLATORS : 40A & 63A in DP, TP & FP version as per

: IS/IEC-60947-3 available.

CHANGEOVER : 25A.&40A in 2 Pole & 4 Pole

ELCB/ RCCB

Single Phase – DP – 16A, 25A, 32A, 40A & 63A in
30m.A, 100m.A & 300m.A

Three Phase – FP – 16A, 25A, 32A, 40A & 63A in
30m.A, 100m.A & 300m.A

Conforms to IS:12640 & IEC/EN:61008



SHEET METAL AC DB BOX

Single Phase – 20A 2Pole Three Phase – 20A
3Pole & 32A 3Pole Conforms IS8623
IS/IEC-60309-1/2 Metal Clad PLUG
& SOCKET also available, seperately.



ON LOAD CHANGE OVER WITH ENCLOSURES



RANGE 63A TO 1000A 415V A.C.
CONFORMS TO IS 8623
ENCLOSURES IP 21 CATEGORY

SWITCH FUSE UNIT (REWIRABLE TYPE)



RANGE 63A TO 1000A 415V A.C.
CONFORMS TO IS 8623
ENCLOSURES IP 21 CATEGORY

SWITH FUSE UNIT (MAIN SWITH) DOUBLE BRAKE SIDE HANDLE (HRC TYPE)



RANGE 63A TO 1000A 415V A.C.
CONFORMS TO IS 8623
ENCLOSURES IP 21 CATEGORY

KNIFE TYPE - CHANGEOVER SWITCH (OFF LOAD)



RANGE 63A TO 1000A 415V A.C.
CONFORMS TO IS 8623
ENCLOSURES IP 21 CATEGORY

CHANGEOVER SWITCH (OFF LOAD)



RANGE 63A TO 1000A 415V A.C.
CONFORMS TO IS 8623
ENCLOSURES IP 21 CATEGORY

PHASE SELECTOR DOUBLE DOOR



Double Door - 4/6/8/12-Ways
(With Rotary Switch , indicator , Wire connection)
Conforms IS/IEC-60309-1/2

ENERGY METER



As per IS 13779 (ISI Marked) Premium high quality moulded Body High Grade Brass terminal RANGE Single Phase - 5A-30A (Available in two models) Three Phase - 10A-40A (Available in both ANALOGUE & LCD displays)

CAPESTERS



ECO Friendly High Insulation Resistance RANGE DRY Can - 2.25mfi - 72mfi Aluminum Oil Can - 2.25mfi - 4mfi

ROTARY SWITCH



Transfers load from one phase to another
RANGE 3WAY with OFF - 1Pole - 32A, 40A & 63A

AUTOMATIC CHANGE OVER



Change the entire LOAD between Mains and Alternate supply Automatically Heavy Duty Built RANGE Single Phase - DP - 32A & 63A Three Phase - TP - 32A, 63A, 100A & 200A

INDUSTRIAL PLUGS & SOCKETS




Conforms IS8623 IS/IEC-60309-1/2 Heavy duty built Available in PBT , Ceramic Both Plug & Socket.

PORCELAIN FUSE UNIT (TYPE A / B)



Conforms to IS 2086/1993 Fine Finish High Grade Porcelain Long Lasting RANGE 16A/240V, 16A-500A/415V

MODULAR CONCEALED BOXES



Made of High strength GI Sheet Provision for Earthing as well Economical pricing RANGE 16 Gauge/1.6mm-2Module-18Module 18 Gauge/1.2mm - 2Module-18Module 20 Gauge/1mm - 2Module-18Module 22 Gauge /0.8mm-2Module-18Module

HRC FUSES HOLDER



Bakelite moulded type fuse Range- 25,32,63,125AMP/415 VOLT

REVERSING SWITCH



High Grade Copper current carrying parts & FR-DMC parts Most successful POINT Style model RANGER/F - 16A Nice, 16A Gold & 32A Gold C/O - 32A 2P, 32A 3P & 32A 4PLT - 32A DP & 32A FP

PVC INSULATION TAPE



PVC TAPE 16mm 6 Meters THICKNESS/0.125mm FIRE RETANDANT

ANMAX ELECTRIC
BAWANA INDUSTRIAL AREA
DELHI-110039
Contact:-8377098104



Since product improvement is a continuing ANMAX policy, specifications of any product are subject to change without prior notice. For further information ask for detail catalogue